



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ
 Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : www.friedmans.co.uk

Technical Data Sheet

Article	Heavyweight Signature Net	
Composition	77% POLYAMIDE 23% ELASTANE	
Weight m ² (+/- 5%)	170 g/m²	
Weight g/lm (+/- 5%)	272g/lm	
Total width (+/- 2%)	160 cm	
Dimensional stability washing 40° C	UNE EN ISO 5077	
	Warp max. 5%	Weft max. 5%
Elasticity	BS 4952:1992	
	Warp 150 % ± 15 %	Weft 110 % ± 15 %
Abrasion (9kPa)	UNE EN ISO 12947-2	>300.000 cycles

Care labelling codes:



Notes:

Technical Specification details prior to a foil application.

Please note due to the numerous different Industries we supply; we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests

We recommend testing each dye bath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ
 Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : www.friedmans.co.uk

Technical Data Sheet

Article	Heavyweight Signature Net	
Composition	77% POLYAMIDE 23% ELASTANE	
Weight m ² (+/- 5%)	170 g/m²	
Weight g/lm (+/- 5%)	272g/lm	
Total width (+/- 2%)	160 cm	
Dimensional stability washing 40° C	UNE EN ISO 5077	
	Warp max. 5%	Weft max. 5%
Elasticity	BS 4952:1992	
	Warp 150 % ± 15 %	Weft 110 % ± 15 %
Abrasion (9kPa)	UNE EN ISO 12947-2	>300.000 cycles

Care labelling codes:



Notes:

Technical Specification details prior to a foil application.

Please note due to the numerous different Industries we supply; we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests

We recommend testing each dye bath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.