


Technical Data Sheet

Article	Renew Prime	
Composition	65% POLYAMIDE (recycled) 35% ELASTANE	
Weight m ² (+/- 5%)	190 g/m²	
Weight linear m. (+/- 5%)	285 g/m lin.	
Total width (+/- 2%)	150 cm	
Dimensional Stability – Washing 40° C BS EN ISO 6330 @40°C - flat dry	width -5% MAX	length -5% MAX
– Steam	width -3% MAX	length -3% MAX
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric 4/5	on wool 3/4
Stretch to Dynamometer (+/- 10%) ZWICK – load 1.5 kg - size of the tested sample: 100 mm x 50 mm		
Plain dyed	width 80% (min 72% - max 88%)	length 70% (min 63% - max 77%)
<i>Modulus 40%</i> Plain dyed	width 350-650g	length 345-640g

Care labelling codes:



Recycled
Yarn



Ultra Chlorine
Resistant



Sun Creams and
Oil Resistant



Shape
Retention



Perfect Fit



Excellent UV
Protection



Excellent
Coverage



Pilling Resistant



Two-way
Stretch



Non Curling



Breathable

Notes:

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests.

We recommend testing each dyebath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.