




Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ  
 Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : [www.friedmans.co.uk](http://www.friedmans.co.uk)

### Technical Data Sheet

Article	<b>Rib Shiny</b>	
Composition	<b>92% POLYAMIDE 8% ELASTANE</b>	
Weight m <sup>2</sup> (+/- 5%)	<b>205 g/m<sup>2</sup></b>	
Weight linear m. (+/- 5%)	<b>256 g/m lin.</b>	
Total width (+/- 2%)	<b>125 cm</b>	
Dimensional Stability – Washing 40° C BS EN ISO 6330 - flat dry	width <b>-18% MAX</b>	length <b>-5% MAX</b>
Steam	width <b>-9% MAX</b>	length <b>-4% MAX</b>
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric <b>4/5</b>	on wool <b>2/3</b>
Stretch to Dynamometer (+/- 10%) ZWICK – load 1,5 kg – strip test – size of tested sample 100mm x 50mm		
Plain dyed	width <b>170%</b> (min 153% - max 187%)	length <b>85%</b> (min 77% - max 94%)
<i>Modulus 40%</i> Plain dyed	width <b>65-115g</b>	length <b>165-315g</b>

Care labelling codes:



Sun Creams and  
Oil Resistance



Perfect Fit



Two-way  
Stretch



Excellent UV  
Protection



Excellent  
Coverage



Extra Comfort



Ultra-Flat

#### Notes:

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests.

We recommend testing each dyebath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.