



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ
 Tel: 0161 975 9002 Email: sales@friedmans.co.uk Web: www.friedmans.co.uk

Technical Data Sheet

Article	Super Stretch PVC
Composition	80% NYLON 20% SPANDEX (PVC Coating)
Weight m ² (+/- 5%)	230 g/m² (3% tolerance)
Total width (+/- 2%)	150 cm (135cm usable)

32G 2BAR TRICOT KNIT

Handwash with cold water. Avoid spin dry.

Notes:

Technical Specification details prior to a foil application.

Please note due to the numerous different Industries we supply; we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests.

We recommend testing each dye bath before any treatment or application other than cutting and sewing. To improve our products, we reserve the right to modify these, as and when necessary.



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ
 Tel: 0161 975 9002 Email: sales@friedmans.co.uk Web: www.friedmans.co.uk

Technical Data Sheet

Article	Super Stretch PVC
Composition	80% NYLON 20% SPANDEX (PVC Coating)
Weight m ² (+/- 5%)	230 g/m² (3% tolerance)
Total width (+/- 2%)	150 cm (135cm usable)

32G 2BAR TRICOT KNIT

Handwash with cold water. Avoid spin dry.

Notes:

Technical Specification details prior to a foil application.

Please note due to the numerous different Industries we supply; we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests.

We recommend testing each dye bath before any treatment or application other than cutting and sewing. To improve our products, we reserve the right to modify these, as and when necessary.